VIISAN

Google EDLA
CERTIFIED

FB-K6 Series

Google EDLA–Certified Interactive Flat Panel For Immersive Classroom Learning

| Android 16 Operating System | 4K Professional 4K Display | Dual-50MP Camera | 50 Touch Points | Anti-Glare Screen | 8-Core Processor 8GB RAM /128GB ROM | ViiTalk Rooms Video Conferencing | Wireless Casting | Interactive Whiteboard |

The FB-K6 Series is an EDLA-certified interactive flat panel designed for modern classrooms. It fully supports Google Workspace apps, including Google Classroom, Docs, Drive, and Meet—allowing teachers to plan and deliver lessons using tools they already know. Powered by Android 16 with 8GB RAM and 128GB of internal storage, the panel delivers smooth performance and fast access to educational applications. It also features a built-in Power Whiteboard for intuitive writing and annotation, along with an integrated Screen Casting app for quick and seamless wireless sharing.

FB-K6 IFPD Specifications

65"

75"

86"

Display

Model	FB-K6 65	FB-K6 75	FB-K6 86
Available Size (Inch)	65"	75"	86"
Dimension (mm)	1504 x 925 x 117mm	1726 x 1050 x 117mm	1972 x 1200 x 117
Brightness (typ)	350 cd/m2	350 cd/m2	350 cd/m2
Color Gamut (typ)	72% NTSC	72% NTSC	72% NTSC
Contrast Ratio	1200:1 (IPS) / 4000:1 (VA)	1200:1 (IPS) / 4000:1 (VA)	1200:1 (IPS) / 4000:1 (VA)
Backlight	DLED	DLED	DLED
Resolution	Ultra HD 3840x2160	Ultra HD 3840x2160	Ultra HD 3840x2160
Aspect Ratio	16:09	16:09	16:09
Response Time	8ms	8ms	8ms
Viewing Angle	178°	178°	178°
Color Depth	8-bits	8-bits	8-bits
Panel Refresh Rate	60Hz	60Hz	60Hz
Others	Low Blue Light	Low Blue Light	Low Blue Light

Touch

Touch Technology	Infrared
Glass	Anti-Glare Glass
Writing Tool	Stylus / Finger / Eraser
Touch Points	Up to 50-point precise touch
Writing Features	Pen Tip Writing

Speaker / Camera / Microphone

Speaker	L：15W / R：15W
Camera	Built-in Dual 50MP Cameras
Microphone	Built-in 8-Microphone Array with AGC / ANR / AEC (10M sound-pickup)

Computing

Operating System	Android 16
CPU	RK3576 (4 × Cortex-A72 + 4 × Cortex-A53)
GPU	Mali-G52 MC3
RAM	8GB
ROM	128GB
UI	4K

I/O

Front	USB-B 2.0 (Touch) x 1 / HDMI IN x 1 / USB-A 3.0 (Public) x 1 / USB-A 2.0 (Public) x 1 / USB-C x 1
Rear	USB-B 2.0 (Touch) x 2 / HDMI-IN x 2 / DP Port x 1 / HDMI OUT x 1 / USB-C IN x 1 / USB-C OUT x 1 USB-A 3.0 (Public) x 2 / USB-A 2.0 (Android) x 1 / TF Card Slot x 1
Bottom	RS232 x 1 / MIC IN x 1 / COAXIAL x 1 / Earphone jack x 1 / LAN IN / OUT x 1
Sensor	Light sensor / IR Receiver
Connectivity	Dual-band 2.4G/5G Wi-Fi 6 (802.11a/b/g/n/ac/ax) +Bluetooth 5.4 ; 10/100/1000 Mbps Ethernet

Optional Accessories

GT282C
4K Wireless
Screen Sharing Dongle

OPS
Intel 12th Gen.
Core i5 or i7 CPU

KZH11
Standard Mobile Stand

Website: www.viisan.com

VIISAN Technology Co., Ltd.
Room 106, 1st Floor, Building 1, No. 20 Tongji South Road,
Beijing Economic-Technological Development Area (BDA),
China (100176) Technical support: info@viisan.com

2/10/2026 V1.2